

## Capacidades y Dimensiones (Generales)

MODELO	TONELADAS DE ENFRIAMIENTO	CANTIDAD VENTILADORES	MOTOR (HP)	DIMENSIONES (m)			PESO (Libras) Aprox.		DIÁM. CONEXIÓN	
				ANCHO	LARGO	ALTO	OPERACIÓN	ENVÍO	ENTRADA	SALIDA
NXF-75	75	1	3.0	2.26	2.24	2.37	4010	1500	8"	8"
NXF-90	90	1	5.0	2.26	2.24	2.37	4020	1510	8"	8"
NXF-100	100	1	7.5	2.26	2.24	2.37	4060	1550	8"	8"
NXF-115	115	1	5.0	2.26	2.85	2.98	6010	2100	8"	8"
NXF-130	130	1	7.5	2.26	2.85	2.98	6030	2140	8"	8"
NXF-150	150	1	10.0	2.26	2.85	2.98	6050	2180	8"	8"
NXF-150-2	150	2	3.0	2.26	4.85	2.37	8020	2800	2 (4")	8"
NXF-180-2	180	2	5.0	2.26	4.85	2.37	8040	2840	2 (4")	8"
NXF-200-2	200	2	7.5	2.26	4.85	2.37	8080	2880	2 (4")	8"
NXF-230-2	230	2	5.0	2.26	5.46	2.98	11900	4000	2 (4")	8"
NXF-260-2	260	2	7.5	2.26	5.46	2.98	11940	4080	2 (4")	8"
NXF-300-2	300	2	10.0	2.26	5.46	2.98	11980	4120	2 (4")	8"

Dimensiones de referencia, para obtener medidas reales se debe consultar al asesor de ventas

**IM SERIE NXF**  
 Capacidad nominal  
 75 a 300 Toneladas  
 95°F / 85°F / 78°F

